



No. of Contacts n	A	B
1	—	2.54
2	2.54	5.08
3	5.08	7.62
4	7.62	10.16
5	10.16	12.7
6	12.7	15.24
7	15.24	17.78
8	17.78	20.32
9	20.32	22.86
10	22.86	25.4
11	25.4	27.94
12	27.94	30.48
13	30.48	33.02
14	33.02	35.56
15	35.56	38.1
16	38.1	40.64
17	40.64	43.18
18	43.18	45.72
19	45.72	48.26
20	48.26	50.8
21	50.8	53.34
22	53.34	55.88
23	55.88	58.42
24	58.42	60.96

NOTE 1

PART NO.	Contact Plating
Z-149- (n) P	0.7 $\mu$ m Gold (Contact Area)
DIC-149- (n) P	Over Nickel
Z-149A- (n) P	0.4 $\mu$ m Gold (Contact Area)
DIC-149A- (n) P	Over Nickel

③								
②			2	Contact	Brass	n	NOTE 1.	—
①			1	Insulator	66Nylon	1	—	UL94V-0 Black

LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
------	------	----	------	----------	-----	-----------	----------	-----	--------	------

DATE	SCALE	UNIT	3RD. A. P	HONDA TSUSHIN KOGYO CO., LTD.						
OCT. 3. 1997	2 / 1	mm (INCH)								
APP. DATE & REV.										
DR.	DE.	CHK.	CHK.	APP.	NAME		MALE CONNECTOR			
M. KASHIHARA	M. KASHIHARA	C. NUNOKAWA	H. EBIHARA	M. TAKAHASHI	PART NO.		Z-149 ( ) - (n) P (DIC-149 ( ) - (n) P)			