



1. CONTACT PLATING
MATING AREA: GOLD PLATING 0.76μm MIN.
TERMINATION AREA: GOLD PLATING 0.05μm
UNDERPLATING: NICKEL PLATING 1.3μm MIN.
2. MATING CONNECTOR
HDR-E14MSG1+
HDR-E14MAG1+
3. SPECIFICATION
RATED CURRENT 0.5A
RATED VOLTAGE 125V AC (r. m. s.)
4. CABLE
WIRE SIZE 30AWG (7/0.1)
INSULATION DIA. Ø0.58 MAX.
5. TWO CABLE HOUSINGS ARE SUPPLIED WITH A CONNECTOR.

6	CABLE HOUSING	PBT	2	————	UL94V-0 BLACK
5	SPACER	PBT	2	————	UL94V-0 BLACK
4	SQR. NUT	BRASS	2	NICKEL PLATING	M2x0.4
3	SHELL	STEEL	1	NICKEL PLATING	————
2	CONTACT	PHOSPHOR BRONZE	14	SEE NOTE #1	————
1	INSULATOR	PBT	1	————	UL94V-0 BLACK

LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
	DATE		SCALE		UNIT	3RD. A. P	HONDA TSUSHIN KOGYO CO., LTD.			
	May. -11.2011		2 / 1		mm (INCH)					
	APP. DATE&REV.									
	DR.	DE.	CHK.	CHK.	APP.	NAME	0.8mm SPACING FEMALE CONNECTOR (PANEL MOUNT TYPE)			REV.
	Y. KATO	Y. KATO	—	—	C. NUJOKAWA	PART NO.	HDR-EC14PFAG1+			