



CONTACT DETAIL

1. CONTACT PLATING
 MATING AREA: 0.76 MICRO METERS MINIMUM GOLD PLATING
 TERMINATION AREA: 0.05 MICRO METERS MINIMUM GOLD PLATING
 UNDERPLATING: NICKEL PLATING
2. APPLICABLE HOOD
 HDR-26LPH ()
3. MATING CONNECTOR
 HDR-EA26LMY () G1+
 HDR-E26M () G1+
4. SPECIFICATION
 RATED CURRENT 0.5A
 RATED VOLTAGE 125V AC (r. m. s.)

HTTK

The product information and this data is for reference only.
 This is subject to change without notice.
 Contact our sales staff for further information before considering or ordering any of our products.
 Please request Engineering Drawing for the most current and accurate design information.

LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE	
					4	SPACER	PA9T (GF)	1	—	UL94V-0 BLACK	
					3	INSULATOR	PA9T (GF)	1	—	UL94V-0 BLACK	
					2	SHELL	STEEL	1	NICKEL PLATING	—	
					1	FEMALE CONTACT	PHOSPHOR BRONZE	26	NOTE#1	—	
					DATE		SCALE	UNIT	3RD. A. P		
					Feb. 22, 2007		3 / 1	mm (INCH)	HONDA TSUSHIN KOGYO CO., LTD.		
					APP. DATE&REV.				NAME		
					DR. DE. CHK. CHK. APP.				0.8mm SPACING SHIELDED FEMALE CABLE CONNECTOR (RoHS)		
					Y. KATO Y. KATO		C. NUNOKAWA H. EBIHARA		PART NO. HDR-E26FSG1+		REV.