



- 1. CONTACT PLATING
MATING AREA: 0.76 MICROMETERS MINIMUM GOLD PLATING
TERMINATION AREA: 0.05 MICROMETERS MINIMUM GOLD PLATING
UNDERPLATING: NICKEL PLATING
- 2. APPLICABLE HOOD
HDR-E26LP () (+)
HDR-E26ALPA+

- 3. MATING CONNECTOR
HDR-EA26LFY () G1+
HDR-EC26LFDT () +
HDR-EC26FDT () +
- 4. SPECIFICATION
RATED CURRENT 0.5A
RATED VOLTAGE 125V AC (r. m. s.)

△3					4	SPACER	PA9T (GF)	1	—	UL94V-0 BLACK
△2					3	INSULATOR	PBT (GF)	1	—	UL94V-0 BLACK
△1					2	SHELL	STEEL	1	NICKEL PLATING	—
					1	MALE CONTACT	PHOSPHOR BRONZE	26	NOTE#1	—
LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
	DATE		SCALE		UNIT	3RD. A. P	HONDA TSUSHIN KOGYO CO., LTD.			
	May. 27, 2007		3 / 1		mm (INCH)					
	APP. DATE&REV.									
	DR.	DE.	CHK.	CHK.	APP.	NAME	0.8mm SPACING SHIELDED MALE CABLE CONNECTOR			REV.
	Y. KATO	Y. KATO	—	—	K. KASHIO	PART NO.	HDR-E26MSG+			