



- 1. CONTACT PLATING  
MATING AREA: 0.76 MICROMETERS MINIMUM GOLD PLATING  
TERMINATION AREA: 0.05 MICROMETERS MINIMUM GOLD PLATING  
UNDERPLATING: NICKEL PLATING
- 2. APPLICABLE HOOD  
HDR-26LPH ( )

- 3. MATING CONNECTOR  
HDR-EA26LFY ( ) G1+  
HDR-E26LFY ( ) G1+  
HDR-EC26LFDT ( ) +
- 4. SPECIFICATION  
RATED CURRENT 0.5A  
RATED VOLTAGE 125V AC (r. m. s.)

LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
△	Apr. 23 2007	Y. K		SHAPE (SPACER)	4	SPACER	PA9T (GF)	1	—	UL94V-0 BLACK
△	MAR. 17 2006	M. M		REVISE	3	INSULATOR	PBT (GF)△	1	—	UL94V-0 BLACK
△	JUN. 19 2005	M. M		CHANGE MATERIAL AND FORM	2	SHELL	STEEL	1	NICKEL PLATING	—
△					1	MALE CONTACT	PHOSPHOR BRONZE	26	NOTE#1	—

  

DATE		SCALE		UNIT		3RD. A. P		HONDA TSUSHIN KOGYO CO., LTD.			
Oct. 20. 2004		3 / 1		mm (INCH)							
APP. DATE & REV.											
DR.	DE.	CHK.	CHK.	APP.	NAME		0.8mm SPACING SHIELDED MALE CABLE CONNECTOR				
Y. KATO	M. MIYAZAKI	—	C. NUNOKAWA	K. KASHIO	PART NO.		HDR-E26MSG1+△				
										REV.	
										3C	