



CONTACT DETAIL

1. CONTACT PLATING
MATING AREA: 0.76 MICRO METERS MINIMUM GOLD PLATING
TERMINATION AREA: 0.05 MICRO METERS MINIMUM GOLD PLATING
UNDERPLATING: NICKEL PLATING
2. APPLICABLE HOOD
HDR-E50LPH
3. MATING CONNECTOR
HDR-EC50LFDT () () +
4. SPECIFICATION
RATED CURRENT 0.5A
RATED VOLTAGE 125V AC (r. m. s.)

					4	SPACER	PA9T (GF)	1	—	UL94V-0 BLACK
					3	INSULATOR	PBT (GF)	1	—	UL94V-0 BLACK
					2	SHELL	STEEL	1	NICKEL PLATING	—
					1	MALE CONTACT	PHOSPHOR BRONZE	50	NOTE#1	—
LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
	Mar. 13, 2006		3	3 / 1						
APP. DATE&REV.					3RD. A. P					
					HONDA TSUSHIN KOGYO CO., LTD.					
DR.	DE.	CHK.	CHK.	APP.	NAME		0.8mm SPACING SHIELDED MALE CABLE CONNECTOR			
Y. KATO	Y. KATO	—	—	H. EBIHARA	PART NO.		HDR-E50MSG1+			
					REV.					