



RECOMMENDED
PANEL CUT-OUT DIMENSIONS
(t=1.12±0.08)

NOTE #1. CONTACT PLATING
CONTACT AREA: Pd/Ni 0.5µm + GOLD 0.1µm MIN.
TERMINAL AREA: GOLD 0.05µm
ALL OVER NICKEL PLATED.
#2. TWO LOCK SCREWS (ITEM#7) ARE
SUPPLIED WITH A CONNECTOR.

RECOMMENDED P. C. B. LAYOUT
(MOUNT SIDE VIEW)
(SCALE=3/1)

DETAIL A
(SCALE=5/1)

7	LOCK SCREW	STEEL	2	NICKEL PLATING	M2x0.4
6	HOLD DOWN	PHOSPHOR BRONZE	2	NICKEL PLATING	
5	SQR. NUT	BRASS	2	NICKEL PLATING	M2x0.4
4	SHELL	STEEL	1	NICKEL PLATING	
3	INSULATOR	PPS	1		UL94V-0 BLACK
2	CONTACT	PHOSPHOR BRONZE	100	SEE NOTE 1	
1	BRACKET	PPS	1		UL94V-0 BLACK

LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
	SEP. 30. 1998		2 / 1							
DR.	DE.	CHK.	CHK.	APP.	HONDA TSUSHIN KOGYO CO., LTD.					
Y. KATO	Y. KATO	—	C. NUNOKAWA	H. EBIHARA	NAME	0.8mm SPACING 100POS. R/A FEMALE CONNECTOR				
PART NO.						HDRA-E100LFDT-SL+		REV.		