



RECOMMENDED P. C. B. LAYOUT  
(MOUNT SIDE VIEW)  
(SCALE=5/1)

NOTE  
1. CONTACT PLATING  
CONTACT AREA: Pd/Ni 0.5µm  
+GOLD 0.1µm MIN.  
TERMINAL AREA: GOLD 0.05µm  
ALL OVER NICKEL UNDERPLATED

PANEL CUT-OUT DIMENSIONS  
(t=1.12±0.08)

9	PROTECT COVER	PPS	1		UL94V-0 BLACK
8	INSULATOR B	LCP	4		UL94V-0 BLACK
7	SPACER	STAINLESS STEEL	1	NICKEL PLATING	
6	BOARD LOCK	PHOSPHOR BRONZE	2	NICKEL PLATING	
5	SQR. NUT	BRASS	4	NICKEL PLATING	M2x0.4
4	SHELL	STEEL	2	NICKEL PLATING	
3	INSULATOR A	PPS	1		UL94V-0 BLACK
2	CONTACT	PHOSPHOR BRONZE	200	SEE NOTE 1	
1	BRACKET	PPS	1		UL94V-0

LTR.	DATE	BY	REV.	DESCRIP	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
	Mar. 15. 2004									
APP. DATE&REV.						HONDA TSUSHIN KOGYO CO., LTD.				
DR.	DE.	CHK.	CHK.	APP.	NAME 0.8mm SPACING 100 POS. R/A DUAL STACKING FEMALE CONNECTOR					
Y. KATO	Y. KATO		C. NUNOKAWA	H. EBIHARA	PART NO. HDRA-E100W ( ) LFDT1EC+					
										REV.

HDRA-E100W2LFDT1EC+	3.4	3.6	2.4	BROWN
HDRA-E100W1LFDT1EC+	2.08	2.28	1.6	BLACK
PART No.	A	B	P.C.B THICKNESS	COLOR OF BRACKET