



RECOMMENDED P. C. B. LAYOUT
(MOUNT SIDE VIEW)
(SCALE=5/1)

掲載している製品の特性及び仕様は参考値です。特性及び仕様については、予告無く変更する場合があります。採用のご検討やご注文の際は弊社担当窓口までお問い合わせをお願いします。納入仕様書の取り交しをお願いします。
The product information in this data is for reference only. This is subject to change without notice. Contact our sales staff for more information before considering or ordering any of our products. Please request Engineering Drawing for the most current and accurate design information.

HTTK

NOTE 1. CONTACT PLATING
CONTACT AREA: GOLD 0.1 μm MIN. OVER PALLADIUM/NICKEL 0.5 μm
TERMINAL AREA: GOLD 0.05 μm
ALL OVER NICKEL UNDERPLATED.
2. CONTACTS ARE INSERT MOLDED.

7	BOARD LOCK	PHOSPHOR BRONZE	2	NICKEL	
6	LOCK SCREW	STEEL	2	NICKEL	
5	SQR. NUT	BRASS	2	NICKEL	M2x0.4
4	SHELL	STEEL	1	NICKEL	
3	INSULATOR	LCP	1		UL94V-0 BLACK
2	CONTACT	PHOSPHOR BRONZE	36	SEE NOTE 1	
1	BRACKET	PPS	1		UL94V-0 BLACK

LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
	DATE			SCALE		UNIT				
	Dec. 26. 2006			2 / 1		mm (INCH)				3RD. A. P
	APP. DATE & REV.					HONDA TSUSHIN KOGYO CO., LTD.				
	DR.	DE.	CHK.	CHK.	APP.	NAME	0.8mm SPACING 36POS. R/A FEMALE CONNECTOR			
	Y. KATO	Y. KATO	—	—	H. EBIHARA	PART NO.	HDRA-EA36LFDT-SLE+			REV.