



RECOMMENDED
PANEL CUT-OUT DIMENSIONS
(t=1.12±0.08)

NOTE 1. CONTACT PLATING
 CONTACT AREA: GOLD 0.1 μm MIN. OVER PALLADIUM/NICKEL 0.5 μm
 TERMINAL AREA: GOLD 0.05 μm
 ALL OVER NICKEL UNDERPLATED.

TOLERANCES UNLESS OTHERWISE SPECIFIED	
DECIMALS	. X ± .3
	. XX ± .13
	. XXX ± .051

5	HOLD DOWN	PHOSPHOR BRONZE	2	NICKEL PLATING	—
4	SHELL	STEEL	1	NICKEL PLATING	—
3	INSULATOR	PA9T	1	—	UL94V-0 BLACK
2	CONTACT	PHOSPHOR BRONZE	68	SEE NOTE 1	—
1	BRACKET	PPS	1	—	UL94V-0 BLACK

LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
	DATE									
	Jun. 10. 2004									
	SCALE									
	2 / 1									
	UNIT									
	mm (INCH)									
	3RD. A. P									
APP. DATE & REV.							HONDA TSUSHIN KOGYO CO., LTD.			
DR.	DE.	CHK.	CHK.	APP.	NAME	0.8mm SPACING 68POS. R/A FEMALE CONNECTOR (ONE MOLD TYPE)				
Y. KATO	Y. KATO	—	C. NUNOKAWA	H. EBIHARA	PART NO.	HDRA-EC68LFDT+				REV.