



The product information in this data is for reference only.
 This is subject to change without notice.
 Contact our sales staff for further information before considering or
 ordering any of our products.
 Please request Engineering Drawings for most current and accurate
 design information.

HTK

6	HOLD DOWN	PHOSPHOR BRONZE	2	NICKEL PLATING	M2 X 0.4
5	GUIDE PIN	STEEL	2	NICKEL PLATING	—
4	SHELL	STEEL	1	NICKEL PLATING	—
3	INSULATOR	PA9T	1	—	UL94V-0 BLACK
2	CONTACT	PHOSPHOR BRONZE	68	SEE NOTE 1	—
1	BRACKET	PPS	1	—	UL94V-0 BLACK

LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
	DATE									
	Apr. 16.2007									
	SCALE									
	2 / 1									
	UNIT									
	mm (INCH)									
	3RD. A. P									
	HONDA TSUSHIN KOGYO CO., LTD.									
	APP. DATE & REV.									
	DR.	DE.	CHK.	CHK.	APP.	NAME	0.8mm SPACING 68POS. R/A FEMALE CONNECTOR (ONE MOLD TYPE)			
	Y. KATO	Y. KATO	—	C. NUNOKAWA	H. EBIHARA	PART NO.	HDBA-EC68LFDT-GP+ REV.			

NOTE 1. CONTACT PLATING
 CONTACT AREA: GOLD 0.1 μm MIN. OVER PALLADIUM/NICKEL 0.5 μm
 TERMINAL AREA: GOLD 0.05 μm
 ALL OVER NICKEL UNDERPLATED.