



RECOMMENDED
PANEL CUT-OUT DIMENSIONS
($t=1.12 \pm 0.08$)

CONTACT DETAIL
(SCALE=5/1)

6	HOLD DOWN	PHOSPHOR BRONZE	2	NICKEL	
5	SQR. NUT	BRASS	2	NICKEL	M2x0.4
4	SHELL	STEEL	1	NICKEL	
3	CONTACT	PHOSPHOR BRONZE	68	SEE NOTE 1	
2	INSULATOR B	LCP	1		UL94V-0 BLACK
1	INSULATOR A	PPS	1		UL94V-0 BLACK

NOTE1. CONTACT PLATING
 CONTACT AREA: Pd/Ni $0.5 \mu\text{m} + \text{GOLD } 0.1 \mu\text{m MIN.}$
 TERMINAL AREA: GOLD $0.05 \mu\text{m}$
 ALL OVER NICKEL UNDERPLATED

LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
	DATE		SCALE		UNIT	3RD. A. P				
	Apr. 15. 2013		2 / 1		mm (INCH)					
	APP. DATE & REV.									
	DR.	DE.	CHK.	CHK.	APP.	NAME	0.8mm SPACING 68POS. FEMALE CONNECTOR SMT TYPE			
	A. TASHIRO	A. TASHIRO	M. KASAHARA	—	Y. KATO	PART NO.	HDRA-E68FYT+			REV.

HTK HONDA TSUSHIN KOGYO CO., LTD.