



NUMBER OF CONTACT	A±0.2	B+0.1/-0.3
2	2	4.6
3	4	6.6
4	6	8.6
5	8	10.6
6	10	12.6
7	12	14.6
8	14	16.6
9	16	18.6
10	18	20.6
11	20	22.6
12	22	24.6
13	24	26.6
14	26	28.6
15	28	30.6
16	30	32.6
17	32	34.6
18	34	36.6
19	36	38.6
20	38	40.6
21	40	42.6
22	42	44.6
23	44	46.6
24	46	48.6
25	48	50.6

NOTES.

1. PLATING
 CONTACT ZONE: GOLD 0.2 μm
 SOLDERING ZONE: GOLD 0.05 μm
2. "n" SHOWS NUMBER OF CONTACT

HTK

③									
②				2	CONTACT	PHOSPHOR BRONZE	n	NOTE #1	—
①				1	INSULATOR	PBT	1	—	UL94V-0 BLACK

LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
------	------	----	------	----------	-----	-----------	----------	-----	--------	------

DATE JUL. 30 (2004)		SCALE 2/1		UNIT mm (INCH)		3RD. A. P		HONDA TSUSHIN KOGYO CO., LTD.		
APP. DATE & REV.										
DR.	DE.	CHK.	CHK.	APP.	NAME		FEMALE CONNECTOR (RoHS)			
T. ODA	T. ODA	—	C. NUNOKAWA	H. EBIHARA	PART NO.		LPC- () FDSG+			REV.