



Table1. Dimensions A and B

n	A	B	CONTACT NO. DISPLAY
2	2	4	1, 2
3	4	6	1, 3
4	6	8	1, 4
6	10	12	1, 6
8	14	16	1
10	18	20	1, 10
12	22	24	1, 12
20	38	40	1, 10, 12

CONTACT NO. DISPLAY (Table 1)

Table2. CRIMP SOCKET

CONTACT FINISH		COMPATIBLE WIRE
△ TIN PLATING	PART OF GOLD PLATING	
LPC-F104S (-R2)	LPC-F103S (-R2)	AWG# 32
LPC-F114S- (50, 500R)	LPC-F113S- (50, 500R)	
LPC-F104N (-R2)	LPC-F103N (-R2)	AWG# 28~32
LPC-F114N- (50, 500R)	LPC-F113N- (50, 500R)	
LPC-F104L (-R2)	LPC-F103L (-R2)	AWG# 22~26
LPC-F114L- (50, 500R)	LPC-F113L- (50, 500R)	

NOTE1. "n" SHOWS NUMBER OF CONTACTS.

2. THE 8 POS. CONNECTOR CUTS AN INSULATOR AT THE "B" SIZE PART AND MAKES A CONNECTOR.

△									
△	APR.05.2000	T. O	CHANGE OF CONTACT FINISH						
△	DEC.05.2000	K. N	CHANGE OF COMPATIBLE WIRE		INSULATOR	PPO	1	—	UL94V-0 BLACK
LTR.	DATE	BY	REV. DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
DATE		SCALE		UNIT		3RD. A. P			
AUG.07 (1991)		5/1		mm (INCH)					
APP. DATE&REV.					HTK HONDA TSUSHIN KOGYO CO., LTD.				
DR.	DE.	CHK.	CHK.	APP.					
T. ODA	T. ODA	—	C. NUNOKAWA	H. EBIHARA	PART NO.	LPC- () FS01			REV. 2B