



RECOMMENDED PCB LAYOUT  
PCB THICKNESS t=1.6

TABLE 1

PART NO.	A	B
LPC-20PM2L ( )	18	21.2
LPC-26PM2L ( )	24	27.2

TABLE 2

PART NO.	PLATING
LPC- (n) PM2L	TIN/LEAD 2 μm
LPC- (n) PM2LG	GOLD 0.2 μm

NOTE1. "n" SHOWS NUMBER OF CONTACTS.

2. AS FOR THE DIMENTION, SEE TABLE #1.

3	CONTACT B	PHOSPHOR BRONZE	n/2	SEE TABLE #2	—
2	CONTACT A	PHOSPHOR BRONZE	n/2	SEE TABLE #2	—
1	INSULATOR	PA66	1	—	UL94V-0 BLACK

LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
------	------	----	------	----------	-----	-----------	----------	-----	--------	------

DATE	SCALE	UNIT	3RD. A. P
APR. 05 (2005)	5/1	mm (INCH)	
APP. DATE&REV.			

DR.	DE.	CHK.	CHK.	APP.	NAME	MALE CONNECTOR
T. ODA	T. ODA	—	C. NUNOKAWA	H. EBIHARA	PART NO.	LPC- ( ) PM2L ( )
						REV.