



RECOMMENDED P. C. B. LAYOUT  
CONNECTOR MOUNT SIDE

TABLE 1

PART No.	n	A	B	C
LPC-6MY2C ( )	6	4	6	2
LPC-8MY2C ( )	8	6	8	4
LPC-10MY2C ( )	10	8	10	6
LPC-12MY2C ( )	12	10	12	8
LPC-14MY2C ( )	14	12	14	10
LPC-20MY2C ( )	20	18	20	16

NOTE1. "n" Shows number of contacts.

2. Applicable Connector : LPC- (n) FY ( ) + ( ) [RoHS]

TABLE 2

PART No.	PLATING
LPC- (n) MY2C+C	TIN/COPPER (2μm)
LPC- (n) MY2CG+	CONTACT AREA : GOLD (0.2μm) SMT AREA : GOLD (0.05μm)

△3										
△2				2	CONTACT	PHOSPHOR BRONZE	n	SEE TABLE #2	—	
△1				1	INSULATOR	PPS	1	—	UL94V-0 BLACK	
LTR.	DATE	BY	REV.	DESCRIP	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
DATE		SCALE		UNIT		3RD. A. P				
SEP. 7 (2005)		5/1		mm (INCH)		HTK HONDA TSUSHIN KOGYO CO., LTD.				
APP. DATE&REV.						NAME				
DR.	DE.	CHK.	CHK.	APP.	MALE CONNECTOR (SMT TYPE) [RoHS]					
T. ODA	T. ODA	—	C. NUNOKAWA	H. EBIHARA	PART NO. LPC- ( ) MY2C ( ) + ( )					
										REV.