



Connection

Connector Pos. #	Flat cable Conductor No.
1	1
35	2
2	3
36	4
33	65
67	66
34	67
68	68

- Note 1. Contact plating
 Contact area: Gold 0.2 μm Min.
 Termination area: Gold
 Underplating: Nickel
2. Cable characteristics
 0.635 mm spacing flat cable
 AWG#30 (7/0.10)
3. Assembly tools
 Locator plate P/N: MLPT-0006A
 Hand press P/N: RPS-K4

RoHS COMPLIANT

LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE	
					5	Strain relief	PBT (GF)	1		UL94V-0 Black	
					4	Cable housing B	PBT (GF)	1		UL94V-0 Black	
					3	Cable housing A	PBT (GF)	1		UL94V-0 Black	
					2	Contact	Phosphor bronze	68	See Note #1		
					1	Insulator	PBT (GF)	1		UL94V-0 Black	
DATE		SCALE		UNIT		3RD. A. P		HONDA TSUSHIN KOGYO CO., LTD.			
Apr. 11. 2009		2/1		mm (INCH)							
APP. DATE&REV.		DR.		DE.		CHK.		CHK.		APP.	
		T. KAWANO		T. KAWANO		T. SOGO		T. SATO		K. KASHIO	
NAME		PART NO.		PCS type female connector (Daisy chain) (RoHS)		REV.					
		PCS-D68RFA1+									