


HONDA TSUSHIN KOGYO CO., LTD. TOKYO JAPAN		Date	Jul. 27, 2017		
Product Specification TAK series 8 Pos. connector		Approved by	Checked by	Written by	
		<i>H. Aizawa</i>	<i>T. Sogo</i>	<i>T. Kawano</i>	
		H.Aizawa	T.Sogo	T. Kawano	
<u>Connector part No.</u>					
Type		Part No.		Note.	
Cable plug connector		TAK001A08BMF		Crimping type connector with backshell	
Crimping contact		TAK-FGB+		Cable crimping type contact (AWG #24~#28)	
Board receptacle connector		TAK001A08BMM		Shielded Right angle dip type connector	
<u>Specification</u>					
No.	Item	Specification			
1	Current Rating	2 amp D.C. maximum			
2	Voltage Rating	30 volts A.C. (r.m.s.)			
3	Operating Temperature	-40 to +105 degrees C			
4	Storage Temperature	-40 to +105 degrees C			
5	Humidity	85%Rh maximum			
6	Insulation Resistance	When tested in accordance with EIA 364-21, insulation resistance shall be a minimum of 1000 MΩ at 500 volts D.C..			
7	Dielectric Withstanding Voltage	When tested in accordance with Method B of EIA364-20, there shall be no breakdown of insulation or flashover at 500 volts A.C. (r.m.s.) for a minute.			
8	Contact Resistance	When tested in accordance with EIA364-23, contact resistance shall not exceed 50 mΩ without conductor resistance.			
9	Humidity (Steady temperature)	When tested in accordance with II of EIA364-31A test condition A, (Temperature: 40 degrees C , Duration: 168 hours), there shall be no physical damage to the connectors. After the test, the insulation resistance shall be no less than 1000 MΩ and there shall be no breakdown of insulation or flashover at 500 volts A.C. (r.m.s.) for a minute. The contact resistance shall not exceed 50 mΩ as well.			

No.	Item	Specification
10	Thermal Shock	<p>When tested in accordance with EIA364-32A test condition 1, (10 cycles in the environment shown in below program), there shall be no physical damage to the connectors. After the test, the contact resistance shall not exceed 50 mΩ.</p>  <p style="text-align: center;">+105 degrees C</p> <p style="text-align: center;">+25 degrees C</p> <p style="text-align: center;">-55 degrees C</p> <p style="text-align: center;">30 min 30 min</p> <p style="text-align: center;">5 min 5 min</p> <p style="text-align: center;">1 Cycle</p>
11	Vibration	<p>When tested in accordance with EIA364-28B test condition 5 test letter A, (Acceleration: 52.43 m/s² 1cycle: 15 minutes), there shall be no physical damage to the connectors. During the test, there shall be no electrical discontinuity of the test circuit greater than 1 microsecond. (100 mA DC of current is applied to the circuit.) After the test, the contact resistance shall not exceed 50 mΩ.</p>
12	Physical Shock	<p>When tested in accordance with EIA364-27B test condition H (Semi-sine wave, Acceleration: 294 m/s², Standard holding time: 11 msec.), there shall be no physical damage to the connectors. During the test, there shall be no electrical discontinuity of the test circuit greater than 1 microsecond. (100 mA DC of current is applied to the circuit.) After the test, the contact resistance shall not exceed 50 mΩ.</p>
13	Durability	<p>When subjected to 50 cycles of insertion and withdrawal cycles with mating male connector at the rate of 600 cycles per hour, there shall be no evident physical damage to the connectors. After the test, the contact resistance shall not exceed 50 mΩ.</p>
14	High Temperature Life	<p>When tested in accordance with EIA364-17 test condition 3 method A , there shall be no physical damage to the connectors. After the test, the contact resistance shall not exceed 50 mΩ.</p> <p style="text-align: center;">Temperature : +105 degrees C Duration: 250 hours</p>
15	Cold Resistance	<p>When tested in accordance with JIS C 5402 7.9, there shall be no physical damage to the connectors. After the test, the contact resistance shall not exceed 50 mΩ.</p> <p style="text-align: center;">Temperature : -55 degrees C Duration: 250 hours</p>
16	Latch Locking Force	<p>When cable plug with a backshell is pulled from board receptacle connector, latch locking force shall be no less than 70N.</p>